



w.h. Kemp Division

Alumichrom

Description:

Alumichrom is an all-purpose, full-bodied, aluminum paint that produces an exceptionally brilliant, weather resisting metallic finish. It may be used as a prime or finish coat with heat resistance to 600° F., sufficient for radiators and steam piping. It has excellent hiding, spreads quickly and easily. Recommended for use on new or previously painted interior or exterior metal, wood and masonry surfaces.

Product specifics:

Coverage:	Approximately 600 square feet per gallon on smooth surfaces.
Dry-Time:	Normal depending on temperature and humidity, 2-4 hours.
Recoat Time:	8 – 12 hours
Stability:	Soft settling, additives eliminate moisture and gassing.
Regulatory:	Meets all Federal & State VOC requirements.
Shelf Life:	Unopened original container, 1 year.

Application:

Surface to be coated must be clean of all dirt, oils, free of any loose material, and dry. If necessary sandpaper lightly to permit proper adhesion. Clean bare metal with paint thinner or mineral spirits. Remove all rust and scale from metal with a wire brush, scraper or sandblast. **NOTE:** If a RUST-REFORMER is utilized, insure that sufficient oil-based primer is applied before applying the ALUMICHRUM in order to prevent residual acid fumes emitted from the reformer to discolor the metallic finish. Stir the paint thoroughly before and occasionally during use. The product may be applied by brush, roller or spray keeping a wet edge. Make all finish strokes in the same direction to insure proper leafing of the aluminum flake. This overlap will increase brilliance and durability. If thinning is required, obtain the necessary consistency with mineral spirits or paint thinner. In order to comply with regulations for VOCs, do not exceed 10% by volume. To protect from abuse or ambient contaminants, apply a clear oil base top coat such as Rolco Labs Topcoat or other clear non-yellowing oil based varnish. Do not use water based topcoats as the ammonia or alkali ingredients can oxidize the aluminum. Apply at no lower than 50 degrees F.

Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means of ventilation during application and drying. For any additional information read the product MSDS. To avoid spontaneous combustion during storage, close the container after each use and any soiled rags utilized for wiping or clean up should be placed in a water-filled closed metal container. Clean up with mineral spirits or naphtha.

Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

Factors beyond the control of W. H. Kemp Division and its affiliates prevent them from assuming responsibility for damage to property or persons, even when this product is applied according to directions. Test to your satisfaction before using. In no event shall liability of W.H. Kemp Division or Parent Corporation and its marketing affiliates exceed the purchase hereof.

655 Washington Avenue • Carlstadt, New Jersey 07072

Phone: 201-939-7704

866-271-5367

Fax: 201-939-3328