



w.h. Kemp Division

655 Washington Avenue
Carlstadt, NJ 07072

Phone: (201) 939-7704 or (866) 271-5367

FAX: (201) 939-3328

Lustrgild Gold Enamels

Description:

Lustrgild Gold Enamels are bright, rich, pale enamels producing a leaflike smoothness and brilliance. For use on any variety of interior surfaces that are not subject to handling or exterior exposure. It is excellent for picture frames, statuary and other artistic designs. Lustrgild is also available in Copper.

Product specifics:

Coverage: Approximately 500-600 square feet per gallon.

Dry-Time: Depending on temperature and humidity, 45 to 60 minutes.

Dry/touch: 45 minutes.

Recoat: 2 hours. **Recoat: 2 hours.** When recoating, spraying is recommended. The gold/bronze pigment particles lay on the surface and brush recoating may raise or resolute the first coat. Spraying will not produce such action.

Stability: Indefinite, the vehicle will not tarnish the gold/bronze pigment in storage and will not produce gassing.

Application:

Stir contents well before use and occasionally during application. Apply by brush, spray or roller. Prepare the surface so that it is clean, dry, smooth and free of oils, wax or other foreign matter. Prime porous surfaces with oil or latex primer. **NOTE:** If a RUST-REFORMER is utilized, ensure that sufficient oil-based primer is applied before applying the LUSTRGILD in order to prevent acid fumes emitted from the reformer discoloring the metallic finish. Spraying will permit the pigment particles to be deposited with maximum uniformity for color reflection and brilliance. Thinning and clean up can be accomplished with mineral spirits. Do not expose the coating to sulphur fumes, alkalies or sodium solutions as they will react with the copper in the pigments and will cause it to tarnish or discolor to a blackish green. A clear top coat such as Rolco Labs Acrylic Top Coat or other clear varnish applied over the gold will act as a shield or sealer to protect the pigment from intrusion by the above mentioned contaminants. Apply at no lower than 50 degrees F.

Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means of ventilation to prevent overexposure during application and drying. For any additional information read the product MSDS. To avoid spontaneous combustion during storage, close the after each use and any soiled rags utilized for wiping or clean up should be placed in a water-filled closed metal container.

Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

Factors beyond the control of W.H. Kemp and its affiliates prevent them from assuming responsibility for damage to property or persons, even when this product is applied according to directions. Test to your satisfaction before using. In no event shall liability of W.H. Kemp Division or Parent Corporation and its marketing affiliates exceed the purchase hereof.