

## ROLCO AQUA-BRONZE

ROLCO'S AQUA-BRONZE IS A BRONZING LIQUID THAT IS A WATER BASED NON-REACTIVE EMULSION. IT CONTAINS PREMIUM COPOLYMERS OF ACRYLIC AND STYRENE. AQUA-BRONZE WAS FORMULATED AS A BRONZING VEHICLE FOR EXTERIOR AND INTERIOR AREAS.

THIS PRODUCT WHEN USED AS A VEHICLE FOR METALLIC POWDERS WILL PRODUCE BRILLIANT RESULTS WITH A DRYING TIME WITHIN 1 TO 2 HOURS UNDER NORMAL AMBIENT TEMPERATURE AND HUMIDITY.

### DIRECTIONS FOR USE:

SURFACE PREPARATION IS MOST IMPORTANT TO THE DURABILITY AND INTEGRITY OF THE FINISH. ALL SURFACES MUST BE CLEAN, DRY AND FREE FROM CONTAMINANTS SUCH AS OILS, WAXES, DUST AND FINGERPRINTS. INSURE THAT THE SURFACES AND FINISHES HAVE BEEN THOROUGHLY DRIED AND HARDENED. WHEN THERE IS A PREVIOUSLY APPLIED COATING OR FINISH, THE APPLICATOR SHOULD TEST A SMALL AREA FOR COMPATIBILITY BEFORE PROCEEDING.

### APPLICATION:

FOR COLORS SUCH AS GOLD, COPPERS AND OTHER BRONZES, USE 2 TO 2 ½ POUNDS OF THE METALLICS PER GALLON AND 1 TO 1 ½ POUNDS OF ALUMINUM POWDERS PER GALLON.

ADD TO THE METALLIC POWDER A SMALL AMOUNT OF THE BRONZING LIQUID AND STIR UNTIL A SMOOTH PASTE IS PRODUCED. THEN ADD TO THIS PASTE THE BALANCE OF THE BRONZING LIQUID AS REQUIRED. ALLOW THE COMPLETED MIXTURE TO STAND SEVERAL HOURS (PREFERABLY OVER NIGHT) TO LET THE TRAPPED AIR PRODUCED BY THE POWDER TO DISSIPATE.

THE RESULTING FINISHED PAINT CAN BE BRUSHED, ROLLED OR SPRAYED. IF THINNING IS NECESSARY, USE WATER AS NECESSARY.

IDEAL CONDITIONS FOR APPLICATION IS BETWEEN 65 TO 75 DEGREES FARENHEIDT AND 40 TO 60 DEGREES OF RELATIVE HUMIDITY. DIFFERING CONDITIONS CAN AFFECT THE FINAL INTEGRITY OF THE FINISH.

FOR CLEAN UP USE WATER WHILE THE VEHICLE OR PAINT IS WET OR DAMP. IF ALLOWED TO DRY THE RESULTING FILM IS NOT SOLUBLE IN WATER.

FOR FURTHER PROTECTION OF THE FINISH, AFTER IT IS THOROUGHLY DRY, THE APPLICATOR CAN USE THE CLEAR VEHICLE AS IT COMES FROM THE CONTAINER.

THE APPROXIMATE COVERAGE OF THE FINISHED MATERIAL IS BETWEEN 325 TO 350 SQUARE FEET PER GALLON.

THIS PRODUCT IS A WATER BASED EMULSION SYSTEM AND SHOULD BE KEPT FROM FREEZING.

THE CONDITIONS AND USE OF THIS PRODUCT ARE BEYOND ROLCO'S CONTROL. DIRECTIONS, INFORMATION, PERFORMANCE AND RESULTS WHEN USED ALONE OR WITH PRODUCTS OF OTHERS ARE WITHOUT WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED.